

#### **D-Link ANT24-0500**

## **Indoor Omni-Directional Antenna**



- 5 dBi Signal Gain
- 2.4GHz Frequency Range
- Omni-Directional
- Includes Cable that Converts
   N-Female to Reverse SMA

#### Indoor 5 dBi Omni-Directional Antenna

The D-Link ANT24-0500 connects to the DWL-900AP+, DI-614+, DI-714P+, DWL-900AP, DI-714 and DI-713P.

The D-Link ANT24-0500 antenna provides extended coverage for an existing 802.11b wireless local area network (WLAN). The D-Link ANT24-0500 comes with a conversion cable that allows connection directly to the DWL-900AP+ wireless access point, DI-614+ wireless router, DI-714P+ wireless router, DWL-900AP wireless access point, DI-714 wireless router and the DI-713P wire-

less router Rev C1 or later wireless broadband router.

The D-Link ANT24-0500 requires an access point or wireless broadband gateways with a reverse SMA connector. The D-Link ANT24-0500 comes with a conversion cable that allows connection directly to the DWL-900AP+ wireless access point, DI-614+ wireless router, DI-714P+ wireless router, DWL-900AP wireless access point, DI-714 wireless router and the DI-713P wireless router Rev C1 or later wireless broadband router.

## The D-Link ANT24-0500 Includes

Antenna

Manual

Conversion Cable

Mounting Kit

#### **Indoor Omni-Directional Antenna**

# Technical Specifications

#### **Electrical Specifications**

#### **Frequency Range**

2.4 -2.5GHz

#### Gain

5 dBi

#### **VSWR**

2:1 Max

#### **Polarization**

Linear, vertical

#### **HPBW**

- horizontal 360°
- vertical- 32°

#### **Downtilt**

40°

#### **Power Handling**

20W (cw)

#### **Impedance**

50 Ohms

#### Connector

N female

#### Cable

(N-male to RP-SMA plug) - 3 meters - 0.83db lost per meter

### **Environmental & Mechanical Characteristics**

#### **Temperature**

-40°F to 176°F (-40°C to 80°C)

#### Humidity

100%@ 77°F (25°C)

#### **Lightning Protection**

DC ground

#### **Radome Color**

Gray-white

#### **Radome Material**

Fiberglass

#### **Radiator Material**

Micro Striple line

#### Weight

1.76 lbs (0.8kg)

#### **Dimensions**

13 x 0.75 in. (330 x 19mm)

#### **Survival Wind Speed**

112 miles/hr (180 km/hr)

#### Warranty

1 Year





