



— ANT24-0700

7dBi High Gain Omni-Directional Antenna

For 2.4GHz ISM Band Indoor Use

The D-Link ANT24-0700 is a high-Gain omni-directional antenna designed for 2.4GHz ISM band indoor use. This antenna provides high transmission/reception rates for wireless LAN devices operating on the 2.4GHz public industrial, scientific and medical (ISM) frequency band. It can be used with 802.11b and 802.11g wireless LAN devices such as access points and remote routers. This antenna can be used to replace the default antenna of your wireless device to expand its operation range. It can be connected to your wireless device through an extension cable (provided with the antenna), or directly attached to your wireless device.

Product Features

- 7dBi Gain omni-directional antenna
- Compliant with 2.4GHz ISM band
- For indoors use with 802.11b/g wireless devices
- Extends and expands wireless networking environment range to 360 degree coverage in open space and office environment
- Perfect pattern and adjustable angle for best performance result
- 4 flexible installation options: desktop on flat surface, magnetic attached, wall-mounting and direct attachment on wireless device
- Stylish, unique housing design
- Works with 2.4GHz wireless antennas equipped with RP-SMA or RP-TNC connector
- Extension cable provided for flexible and extendable antenna working environment

ANT24-0700

Technical Specifications

2.4GHz Antenna

Electrical Properties

Frequency Range
2.4GHz to 2.5 GHz

Directivity
Omni-directional

Impedance
50 ohm (normal)

VSWR
1.92 (max.)

Return Loss
-10dB (max.)

Antenna Structure
Collinear

Peak Gain
7dBi(without cable loss)

Admitted Power
1 watt

Cable Loss (1.5m)
2.1dB at 2.45GHz

HPBW/E-Plane (Vertical)
24 degrees

HPBW/H-Plane (Horizontal)
360 degrees

Physical & Environmental

Extension Cable
- RG-178 50-ohm
- 1.5-meter length, gray color

Connector
- RP-SMA
- RP-SMA to RP-TNC adapter provided

Antenna Material
ABS, ABS+PC

Color
- Antenna: metallic gray and silver
- Antenna base: metallic gray

Dimensions
326 (H) x 120 (W) x 120 (D) mm (antenna base included)
9 mm (diameter) (antenna pole)

Weight
226 grams (antennabase and extension cable included)

Operating Temperature
-20° to +65°C

Storage Temperature
-30° to +75 °C

Operating Humidity
5% to 95% RH non-condensing

Storage Temperature
5% to 95% RH non-condensing

Ordering Information

ANT24-0700 7dBi Omni-Directional Indoor 2.4GHz Antenna

D-Link®

Specifications subject to change without prior notice.
D-Link is a registered trademarks of D-Link Corporation/D-Link System Inc. All other trademarks belong to their proprietors.

U.S.A	TEL: 1-714-885-6000	FAX: 1-866-743-4905
Canada	TEL: 1-905-8295033	FAX: 1-905-8295223
Europe	TEL: 44-20-8731-5555	FAX: 44-20-8731-5511
Germany	TEL: 49-6196-77990	FAX: 49-6196-7799300
France	TEL: 33-1-30238688	FAX: 33-1-30238689
Netherlands	TEL: 31-10-282-1445	FAX: 31-10-282-1331
Belgium	TEL: 32(0)2-517-7111	FAX: 32(0)2-517-6500
Italy	TEL: 39-2-2900-0676	FAX: 39-2-2900-1723
Iberia	TEL: 34-93-4090770	FAX: 34-93-4910795
Sweden	TEL: 46-(0)8564-61900	FAX: 46-(0)8564-61901
Norway	TEL: 47-23-897189	FAX: 47-22-309085
Denmark	TEL: 45-43-969040	FAX: 45-43-424347
Finland	TEL: 358-9-2707-5080	FAX: 358-9-2707-5081
Singapore	TEL: 65-6774-6233	FAX: 65-6774-6322
Australia	TEL: 61-2-8899-1800	FAX: 61-2-8899-1868
China	TEL: 86-10-5863-5800	FAX: 86-10-5863-5799
India	TEL: 91-022-2652-6696	FAX: 91-022-2652-8914
Middle East (Dubai)	TEL: 9714-3916480	FAX: 9714-3908881
Turkey	TEL: 90-212-335-2553	FAX: 90-212-335-2500
Egypt	TEL: 202-414-4295	FAX: 202-415-6704
Israel	TEL: 972-9-9715700	FAX: 972-9-9715601
Latin America	TEL: 56-2-232-3185	FAX: 56-2-232-0923
Brasil	TEL: 55-11-55039320	FAX: 55-11-55039322
South Africa	TEL: 27-1266-52165	FAX: 271266-52186
Russia	TEL: 7-095-744-0099	FAX: 7-095-744-0099#350
Taiwan	TEL: 886-2-2910-2626	FAX: 886-2-2910-1515
D-Link Corp.	TEL: 886-2-2916-1600	FAX: 886-2-2914-6299