

## DVR-F1104-4M

4MP 4CH 1 SATA HYBRID DVR




### KEY FEATURES

- 1 SATA (Maximum support 6TB)
- Support AHD/TVI/CVI/1080P/4MP
- Support VGA, CVBS, HDMI 1080P HD Output
- Video Compression H.264 High Profile
- 4Ch Audio Input/1 Ch Audio Output

### INTERFACE



### DIMENSION



## SPECIFICATION

### VIDEO

Video Compression	H.264 High Profile
Encode Ability	4ch*4MP@8fps/3MP@10fps(AHD), 4ch*1080P@15fps(5 IN 1)
Decode Ability	4ch*4MP@8fps/3MP@10fps(AHD), 4ch*1080P@15fps(5 IN 1)
Preview Ability	4ch*4MP@15fps(AHD) /4ch*3MP@18fps(AHD) / 4ch*1080P(5 IN 1)
Video Input	Pure Analog: 4ch*4MP@8fps/3MP@10fps(AHD) / 4ch*1080P@15fps/720p(5 IN 1); Mixed Input:4ch*4MP(Analog + IP), Pure Network:4ch*1080P/960P/3MP/4MP;

### AUDIO

Audio Compression	G711A
Two Way Audio	Support

### RECORD AND PLAYBACK

Hard Drive	1 SATA(Each maximum support 6T)
Record	Manual/Event/Timer
Playback	4ch(pure local input mode)

### STORAGE AND BACKUP

Space Occupation	960H:12~20G/ day*channel 720P:10~20G/ day*channel 1080P: 20~30G/ day*channel Audio:691.2M/ day*channel
Backup Mode	USB HDD

### INTERFACE

Video Input	4ch BNC (AHD/TVI/CVI/CVBS)
Video Output	1ch VGA,1ch HDMI,1ch CVBS
Audio Input	4ch RCA
Audio Output	1ch RCA
Alarm Input	N/A
Alarm Output	N/A
Network Interface	1 RJ45 10M/100M Adaptive Ethernet Port
PTZ Control	RS485, Support Multiple PTZ Protocols
USB	2 USB
Hard Disk	1 SATA

### GENERAL

Power	DC12V/2A
Operating Temperature	-10°C ~ 50°C (14°F ~ 122°F)
Dimension	255mm(L)x255mm(W)x45mm(H)
Product Weight	900g