


## DVR-F2108-M1

### 8CH, 2MP Lite DVR




## KEY FEATURES

- 8CH, 1SATA
- Support AHD/TVI/CVI/IP Cameras
- Support AHD/TVI/CVI cameras up to 2MP
- Support H.264+/H.264
- Support Smart Playback & analytics
- Support 2 extra IP Ch
- Support video quality detection (VQD)

# DVR-F2108-M1

8CH, 2MP Lite DVR

## INTERFACE



## SPECIFICATION

### VIDEO & AUDIO INPUT

|                |   |
|----------------|---|
| Video Input    | 8ch BNC interface(1.0Vp-p, 75 Ω)        |
| TVI / CVI /AHD | 1080P, 720P                             |
| IPC            | Up to 8ch 2MP                           |
| Audio Input    | 1-ch, RCA (2.0 Vp-p, 1 KΩ)              |
| Two way Talk   | 1-ch, multiplex with Audio Input (RCA ) |

### VIDEO & AUDIO OUTPUT

|              |   |
|--------------|---|
| HDMI         | 1ch, resolution:<br>1920×1080/60Hz,1280×1024/60Hz,1280×720/60<br>Hz,1024×768/60Hz |
| VGA          | 1ch, resolution:<br>1920×1080/60Hz,1280×1024/60Hz,1280×720/<br>60Hz,1024×768/60Hz |
| CVBS output  | NA  |
| Audio Output | 1-ch, RCA (Linear, 1kΩ)   |

### RECORDING

|                   |   |
|-------------------|---|
| Compression       | H.264/H.264+                                    |
| Resolution        | 8ch 1080P Lite@15fps; 960H1/D1/CIF<br>real time |
| Frame Rate(fps)   | 1fps-15fps                                      |
| Video Bit Rate    | 11Kbps-2707Kbps                                 |
| Record Mode       | Manual, Schedule, Alarm                         |
| Audio Compression | G.711a  |
| Audio Bit Rate    | 64Kbps  |

### PLAYBACK & BACKUP

|               |  |
|---------------|--|
| Playback Mode | Smart Playback/Normal/Time Division/ Label/<br>Event/ Picture Playback |
| Playback Rate | 4ch Playback   |
| Backup Mode   | USB Device/Network   |

### SMART FUNCTION

|                            |  |
|----------------------------|--|
| Smart Detection for Analog | 2CH line crossing detection, area Intrusion                  |
| Smart Playback for Analog  | Line crossing detection, Area Intrusion,<br>Motion detection |
| Online Upgrade             | Supported  |

### NETWORK

|                  |   |
|------------------|---|
| Ethernet         | 1 RJ-45 10/100 Mbps self-adaptive Ethernet<br>interface   |
| Network Function | HTTPs,HTTP,TCP/IP,IPv4,UPnP,Onvif2.6,RTS<br>P,RTCP,UDP,SMTP,SNMP,Multicast,IGMP,N<br>TP,DHCP,DNS,DDNS, FTP, P2P |
| Smart Phone      | IOS (iPhone, iPad), Android (Phone, Pad)  |

| HARD DISK                            |  |
|--------------------------------------|--|
| SATA                                 | 1 HDD                                  |
| Capacity                             | Up to 8TB capacity for each HDD        |
| EXTERNAL INTERFACE                   |  |
| Serial Interface                     | NA                                     |
| USB Interface                        | 2 × USB                                |
| GENERAL                              |  |
| Power Supply                         | DC12V, 1.5A                            |
| Power Consumption                    | ≤10W (without HDD)                     |
| Working Environment                  | -10°C~+55°C / 10%~90%RH                |
| Dimension (W×D×H)                    | 250 x 230 x 45mm                       |
| Weight (without HDD)                 | 1.5kg                                  |
| Certification                        | CE, BIS                                |
| SYSTEM MANAGEMENT                    |  |
| Mobile Software                      | D-Link Smart CCTV App                  |
| Desktop Software                     | DSVS (D-Link Smart Video Surveillance) |
| System Requirement for Web Interface | IE                                     |